

AMENDMENTS TO THE SPECIFICATION:

Please amend the specification as follows:

Please amend the paragraph beginning at page 2, line 9, which starts with "Besides what is described" as follows:

Besides what is described above, there is a telephone set mounting angle varying apparatus wherewith a telephone main body 121 is set in one of two angles using a telephone base 122, as shown in Fig. 38 ~~49~~.

Please amend the paragraph beginning at page 2, line 18, which starts with "With the mounting angle" as follows:

With the mounting angle varying apparatus 120, when the telephone main body 121 is to be mounted with a small angle of inclination relative to the telephone set mounting surface, the setting is made so that the frame 121k in the lower part of the telephone main body 121 is accommodated inside the telephone base 122, and so that the engagement indentation 121o in the lower part of the telephone main body 121 engages the telephone base 122, as shown in Fig. 38(a) ~~49(a)~~.

Please amend the paragraph beginning at page 2, line 25, which starts with "When the telephone main body" as follows:

When the telephone main body 121 is to be mounted with a large angle of inclination relative to the telephone set mounting surface, on the other hand, the setting is made so that the frame 121k at the bottom of the telephone main body 121 is disposed to the outside from the inside of the telephone base 122, and so that the

engagement indentation 121ko of the frame 121k engages the telephone base 122, as shown in Fig. ~~38(b)~~ 49(b).

Please amend the paragraph beginning at page 3, line 3, which starts with "As another telephone" as follows:

As another telephone mounting angle varying apparatus, there is one wherewith a telephone main body 131 is set at a plurality of kinds of angles relative to the telephone mounting surface using a telephone base 132, as shown in Fig. 39 50.

Please amend the paragraph beginning at page 3, line 26, which starts with "As another telephone" as follows:

As another telephone mounting angle varying apparatus, there is one wherewith a telephone main body 141 is set in a plurality of kinds of angles by changing the engagement position of an angle varying lever 1 42r in a telephone base 142, as shown in Fig. 40 51.

Please amend the paragraph beginning at page 4, line 15, which starts with "As another telephone" as follows:

As another telephone mounting angle varying apparatus, there is one wherewith a telephone main body 151 is set in a desired mounting angle by changing the engagement position with an angle varying member attached to a telephone base 152 so as to turn freely, as shown in Fig. 41 52.

Please amend the paragraph beginning at page 5, line 3 which starts with "As another telephone mounting" as follows:

As another telephone mounting angle varying apparatus, there is one wherewith a telephone main body 161 is set in a desired mounting angle by changing the position of an angle varying member 161b attached so that it turns freely to the telephone main body 161, as shown in Fig. 42 53.

Please amend the paragraph beginning at page 5, line 11, which starts with "In order to set the telephone" as follows:

In order to set the telephone main body 161 at a small mounting angle, the angle varying member 161 b is folded against the lower surface portion of the telephone main body 161, as shown in Fig. 42(a) 53(a).

Please amend the paragraph beginning at page 5, line 16, which starts with "In order to set a large" as follows:

In order to set a large mounting angle, on the other hand, the angle 15 varying member 161 b is separated from the lower surface portion of the telephone main body 161 and the other end thereof is made to come up against the mounting surface for the telephone set as shown in Fig. 42(b) 53(b).

Please amend the paragraph beginning at page 6, line 4, which start with "Even with mounting angle" as follows:

Even with mounting angle varying apparatuses wherewith a plurality of 5 mounting angles can be set, in order to set the mounting angle of the telephone main body 131, that must be done while visually verifying the engagement between the angle adjustment holes 131k1 to 13 1k4 and the engagement portion of the telephone base

132, as shown in Fig. ~~39~~ 50, and there is a problem with operability in setting the mounting angle.

Please amend the paragraph beginning at page 6, line 18, which starts with "In the mounting angle" as follows:

In the mounting angle varying apparatuses 130, 140, and 150 shown in Fig. ~~39~~ 41 to ~~44~~ 52, similarly, when changing the angle of the telephone main body, the telephone main body portion separates from the telephone base, and there is a problem in that the product does not have the feel of a high quality product.